

Appl. No. 10/675819
Reply to Office action of 8/22/05
Page 2

IN THE CLAIMS

Amendments To The Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) An arrangement structure of a vehicle door open-close device to automatically open and close a vehicle door by means of a driving force comprising:
 - a roof member provided on a door-opening area for constituting a ceiling member of a vehicle body;
 - a side member provided on the door-opening area for constituting a side portion of the vehicle body; and
 - a connecting part between the roof member and the side member;
 - a strengthening member located below the connecting part between the roof member and the side member and is bridged across the connecting part;
 - wherein said vehicle door open-close device is arranged in a space surrounded by said roof member, said side member, and said strengthening member.

2. (Previously presented) An arrangement structure of a vehicle door open-close device according to claim 1, wherein;
 - said roof member including an outside roof member and an inside roof member;
 - said side member including an outside side member and an inside side member; and
 - said strengthening member is bridged between said inside roof member and said inside side member;
 - wherein said inside roof member and said inside side member are connected to the connecting part in which said outside roof member and said outside side member are connected thereto.

Appl. No. 10/675819
Reply to Office action of 8/22/05
Page 3

3. (Original) The arrangement structure of a vehicle door open-close device according to claim 2, wherein a roof reinforced member provided on said roof member and a side reinforced member provided on said side member are connected to said connecting part.

4. (Previously presented) The arrangement structure of a vehicle door open-close device according to claim 2, wherein an attaching part of said inside side member is attached to an attaching reinforcement member, and said attaching reinforcement member is connected to said connecting part.

5. (Currently amended) The arrangement structure of a vehicle door open-close device according to claim 3, wherein an attaching part of said inside side member is provided with an attaching reinforcement member, and said attaching reinforcement member is connected to said connecting connection part.

6. (Currently amended) The arrangement structure of a vehicle door open-close device according to claim 3, wherein
said roof ~~reinforcement~~ reinforced member is positioned between said outside roof member and said inside roof member, and
said side reinforced member is positioned between said outside side member and said inside side member.

7. (Previously presented) The arrangement structure of a vehicle door open-close device according to claim 1, wherein said strengthening member is formed of a single member.

8. (Previously presented) The arrangement structure of a vehicle door open-close device according to claim 1, wherein said strengthening member is a diagonal beam connecting the roof member and the side member with each other.